

MATERIALS

CONTAINERS

PP		APET		CA+PET		ALc		PLA	
From 0°C to +110°C		From -40°C to +70°C		From -40°C to +200°C		From -40°C to +200°C		From 0°C to +40°C	
APR30T	P1 136 x 95 x 30	GB30PT	P1 137 x 95 x 30	V40P1CB	P1 136 x 95 x 40	VA45Pc	P2 142 x 126 x 45	GD30PT	P1 137 x 95 x 30
APR45T	P1 136 x 95 x 45	GB45PT	P1 137 x 95 x 45	V65P1CB	P1 136 x 95 x 65	VA45Gc	G 196 x 142 x 45	GD45PT	P1 137 x 95 x 45
APR63T	P1 136 x 95 x 63	GB63PT	P1 137 x 95 x 63	V45PC	P2 137 x 122 x 45	VA45Lc	L 233 x 196 x 45	GD63PT	P1 137 x 95 x 63
APN45T	P2 136 x 120 x 45	GB45PNT	P2 137 x 120 x 45	V33GC	G 192 x 140 x 33	VA45Mc	M 266 x 196 x 45	GD45PNT	P2 137 x 120 x 45
APN65T	P2 136 x 120 x 65	GB65PNT	P2 137 x 120 x 65	V45GC	G 192 x 140 x 45			GD65PNT	P2 137 x 120 x 65
APN82T	P2 136 x 120 x 82	GB82PNT	P2 137 x 120 x 82	V75GC	G 192 x 140 x 75			GD82PNT	P2 137 x 120 x 82
AG25T	G 190 x 136 x 25	GB25GT	G 190 x 137 x 25	V45HC	H 214 x 142 x 45	ALbn		GD25GT	G 190 x 137 x 25
AG38T	G 190 x 136 x 38	GB38GT	G 190 x 137 x 38	VR25LC	L 232 x 192 x 25	From -40°C to +200°C		GD38GT	G 190 x 137 x 38
AG50T	G 190 x 136 x 50	GB50GT	G 190 x 137 x 50	V45LC	L 232 x 192 x 45	V45Pabn	P2 142 x 126 x 45	GD50GT	G 190 x 137 x 50
AG70T	G 190 x 136 x 70	GB70GT	G 190 x 137 x 70	VR20MC	M 262 x 192 x 20	V45Gabn	G 196 x 142 x 45	GD70GT	G 190 x 137 x 70
AG85TP	G 190 x 136 x 85	GB85GT	G 190 x 137 x 85	V45MC	M 262 x 192 x 45	V45Labn	L 233 x 196 x 45	GD85GT	G 190 x 137 x 85
ALR25T	L 230 x 190 x 25	GB15LT	L 230 x 190 x 15	CPET		V45Mabn	M 266 x 262 x 45	GD15LT	L 230 x 190 x 15
AL35T	L 230 x 190 x 35	GRB20LTi	L 230 x 190 x 20	From -40°C to +180°C				GD25LT	L 230 x 190 x 25
ALR50T	L 230 x 190 x 50	GB25LT	L 230 x 190 x 25	D45P	P2 136 x 120 x 45	CA+PLA		GD35LT	L 230 x 190 x 35
AL65T	L 230 x 190 x 65	GB35LT	L 230 x 190 x 35	D65P	P2 136 x 120 x 65	From -40°C to +200°C		GD50LT	L 230 x 190 x 50
AMR25T	M 260 x 190 x 25	GB50LT	L 230 x 190 x 50	D38G	G 190 x 136 x 38	V40P1CD	P1 136 x 95 x 40	GD65LT	L 230 x 190 x 65
AMR38T	M 260 x 190 x 38	GB65LT	L 230 x 190 x 65	D50G	G 190 x 136 x 50	V65P1CD	P1 136 x 95 x 65	GD15MT	M 260 x 190 x 15
AMR50T	M 260 x 190 x 50	GB15MT	M 260 x 190 x 15	DT50G	G 190 x 136 x 50	V45PCD	P2 137 x 122 x 45	GD25MT	M 260 x 190 x 25
AM65T	M 260 x 190 x 65	GRB20MTi	M 260 x 190 x 20	D70G	G 190 x 136 x 70	V33GCD	G 192 x 140 x 33	GD35MT	M 260 x 190 x 35
		GB25MT	M 260 x 190 x 25	D38L	L 230 x 190 x 38	V45GCD	G 192 x 140 x 45	GD50MT	M 260 x 190 x 50
		GB35MT	M 260 x 190 x 35	D50L	L 230 x 190 x 50	V75GCD	G 192 x 140 x 75	GD65MT	M 260 x 190 x 65
		GB50MT	M 260 x 190 x 50	DB50L	L 230 x 190 x 50	V45HCD	H 214 x 142 x 45		
		GB65MT	M 260 x 190 x 65	D38M	M 260 x 190 x 38	VR25LCD	L 232 x 192 x 25		
				D50M	M 260 x 190 x 50	V45LCD	L 232 x 192 x 45		
				D65M	M 260 x 190 x 65	VR20MCD	M 262 x 192 x 20		
						V45MCD	M 262 x 192 x 45		

CA+PP

From -40°C to +200°C

V45PCA	P2 137 x 122 x 45
V45GCA	G 192 x 140 x 45
V45LCA	L 232 x 192 x 45
V45MCA	M 260 x 190 x 45

MATERIALS

HEAT SEALING FILMS



TABLE TOP SYSTEM

for Containers

Reference	Characteristics	PP	CA+PP	CA+PET	APET	CPET	ALc	ALbn
B1 T	monolayer / strong seal	X	X					
B1 TNAF	monolayer / strong seal / anti-fog	X	X					
B1 TMF	monolayer / strong seal / microperforated	X	X					
B1 TSB	monolayer / strong seal			X	X	X		
B1 TSBAF	monolayer / strong seal / anti-fog			X	X	X		
B1 TSBMF	monolayer / strong seal / microperforated			X	X	X		
B1 TSPBAF	monolayer / strong seal + peelability / anti-fog			X	X	X		
B1 TPBAF	monolayer / peelable / anti-fog			X	X	X		
B1 TPBAF	mono / pelabile / anti-condensa			X	X	X		
B1 TA	accoppiato / saldante	X	X					X
B1 TAAF	accoppiato / saldante / anti-condensa	X	X					X
B1 TPAAF	accoppiato / pelabile / anti-condensa	X	X					X
B1 TOPAU	accoppiato / pelabile / universale	X	X	X	X	X	X	X
B1 TRBAF	accoppiato / richiudibile / anti-condensa				X			

MATERIALS

HEAT SEALING FILMS



TABLE TOP SYSTEM

for Containers

Reference	Characteristics	CA+PET	APET	CPET	PLA	CA+PLA	ALc
B1 TBFN	monolayer / strong seal / compostable	X	X	X	X	X	
B1 TADFNL	multilayer / strong seal + peelability* / compostable	X	X	X	X	X	X
B1 TAADFNL	multilayer / strong seal + peelability* / anti-fog / compostable	X	X	X	X	X	X

* according to the sealing temperature and/or the container material used, the film can be sealable and/or peelable



Biodegradable and compostable films, in compliance with norm EN13432.

MATERIALS

TRASPARENT LIDS IN APET



Item	Series	(mm) L x B	for Containers			
			APET	CPET	ALbn	ALc
CTU.B.P (P0515)	P2	149 x 132	X	X	X	X
CTU.B.G (G0875)	G	203 x 149	X	X	X	X
CTU.B.L (L1570)	L	240 x 203	X	X	X	X
CTU.B.M (M1820)	M	273 x 203	X	X	X	X

No responsibility is implied or may be linked to this catalog.

All technical data does not have scientific value and are reported only for the purpose technical / application of the product.

Technological suitability: the product must always be verified by the user as regards the technological suitability referring to the production process, the packaging environment and the food to be packaged.

SCAN THE QR CODE AND FIND OUT MORE



COMPANY WITH FOOD SAFETY SYSTEM CERTIFIED BY DNV ISO 22000

COMPANY WITH MANAGEMENT SYSTEM CERTIFIED BY DNV ISO 9001-ISO 14001 ISO 45001



COMPAC PACKAGING

Compac s.r.l.
Via Spallanzani 8/a
42024 Castelnovo di Sotto - RE - Italy
Tel. +39 0522.688.509 / +39 0522.683.873
www.compac.it - info@compac.it