



C1NE

Heat Sealer Machine



Table Top Heat Sealing Machine.
Digital control panel with a setting of temperature and time sealing.
Multi format. Possibility to seal 3 different formats without changing the mold:

- P1 - 137 x 95 mm
- P2 - 137 x 120 mm
- G - 190 x 137 mm


COMPAC SYSTEM

- | | |
|----------------------------------|--------------------------------------|
| ■ Containers in PLA | ■ Containers in CA + PET |
| ■ Containers in APET | ■ Containers in PP |
| ■ Containers in CA + PLA | ■ Containers in CPET |
| ■ Containers in CELLULOSE (PULP) | ■ Containers in ALUMINIUM (ALc/ALbn) |

C1NE

FILM REEL B1

DATA SHEET



- Total weight: 22 Kg. approx. (without reel)
- Power supply: single-phase + earth
- Power voltage: 220 V ± 10%
- Power frequency: 50 Hz
- OVERALL DIMENSIONS mm:
A: 414 B: 207 C: 366 E: 495 L: 620
- MINIMUM DIMENSIONS OF WORKTABLE mm:
F: 195 G: 275
- Format and Film reel used:
CONTAINERS Series P1 - P2 - G
with B1 REELS
width 150mm - MAX Ø 155mm.

MATERIALS

CONTAINERS

PP			APET			CA+PET			ALc			PLA		
APR30T	P1	136 x 95 x 30	GB30PT	P1	137 x 95 x 30	V45PC	P2	137 x 122 x 45	VA45Pc	P2	142 x 126 x 45	GD30PT	P1	137 x 95 x 30
APR45T	P1	136 x 95 x 45	GB45PT	P1	137 x 95 x 45	V33GC	G	192 x 140 x 33	VA45Gc	G	196 x 142 x 45	GD45PT	P1	137 x 95 x 45
APR63T	P1	136 x 95 x 63	GB63PT	P1	137 x 95 x 63	V45GC	G	192 x 140 x 45	ALbn			GD63PT	P1	137 x 95 x 63
APN45T	P2	136 x 120 x 45	GB45PNT	P2	137 x 120 x 45	V75GC	G	192 x 140 x 75	ALbn			GD45PNT	P2	137 x 120 x 45
APN65T	P2	136 x 120 x 65	GB65PNT	P2	137 x 120 x 65	CPET			V45Pabn	P2	142 x 126 x 45	GD65PNT	P2	137 x 120 x 65
APN82T	P2	136 x 120 x 82	GB82PNT	P2	137 x 120 x 82	D45P	P2	136 x 120 x 45	V45Gabn	G	196 x 142 x 45	GD82PNT	P2	137 x 120 x 82
AG25T	G	190 x 136 x 25	GB25GT	G	190 x 137 x 25	D65P	P2	136 x 120 x 65	CA+PLA			GD25GT	G	190 x 137 x 25
AG38T	G	190 x 136 x 38	GB38GT	G	190 x 137 x 38	D38G	G	190 x 136 x 38	V45PCD	P2	137 x 122 x 45	GD38GT	G	190 x 137 x 38
AG50T	G	190 x 136 x 50	GB50GT	G	190 x 137 x 50	D50G	G	190 x 136 x 50	V33GCD	G	192 x 140 x 33	GD50GT	G	190 x 137 x 50
AG70T	G	190 x 136 x 70	GB70GT	G	190 x 137 x 70	DT50G	G	190 x 136 x 50	V45GCD	G	192 x 140 x 45	GD70GT	G	190 x 137 x 70
AG85TP	G	190 x 136 x 85	GB85GT	G	190 x 137 x 85	D70G	G	190 x 136 x 70	V75GCD	G	192 x 140 x 75	GD85GT	G	190 x 137 x 85
PULP														
VP45PU P2 140 x 124 x 45														
VP45GU G 194 x 140 x 45														

MATERIALS

HEAT SEALING FILMS



TABLE TOP SYSTEM			for Containers						
Reference	Characteristics		PP	CA+PET	APET	CPET	ALc	ALbn	PULP
B1	T	monolayer / strong seal	X						
B1	TNAF	monolayer / strong seal / anti-fog	X						
B1	TMF	monolayer / strong seal / microperforated	X						
B1	TSB	monolayer / strong seal		X	X	X			
B1	TSBAF	monolayer / strong seal / anti-fog		X	X	X			
B1	TSBMF	monolayer / strong seal / microperforated		X	X	X			
B1	TSPBAF	monolayer / strong seal + peelability / anti-fog		X	X	X			
B1	TPBHAF	monolayer / peelable / anti-fog		X	X	X			
B1	TA	multilayer / strong seal	X					X	X
B1	TAAF	multilayer / strong seal / anti-fog	X					X	X
B1	TPU	multilayer / peelable / universal	X	X	X	X	X	X	X
B1	TPUMAF	multilayer / peelable / anti-fog / universal	X	X	X	X	X	X	X

MATERIALS

HEAT SEALING FILMS



TABLE TOP SYSTEM			for Containers			
Reference	Characteristics		PLA	CA+PLA	PULP	ALc
B1	TBFN	monolayer / strong seal / compostable	X	X		
B1	TADFN	multilayer / peelable / compostable	X	X	X	X



Biodegradable and compostable films, in compliance with norm EN13432.

MATERIALS

TRASPARENT LIDS IN APET



TABLE TOP SYSTEM			for Containers				
Item	Series	(mm) L x B	PP	APET	CPET	ALbn	ALc
CTU.B.P (P0515)	P2	149 x 132	X	X	X	X	X
CTU.B.G (G0875)	G	203 x 149	X	X	X	X	X

No responsibility is implied or may be linked to this catalog. All technical data does not have scientific value and are reported only for the purpose technical / application of the product. Technological suitability: the product must always be verified by the user as regards the technological suitability referring to the production process, the packaging environment and the food to be packaged.

Compac s.r.l.
Via Spallanzani 8/a
42024 Castelnovo di Sotto - RE - Italy
Tel. +39 0522.688.509
Fax +39 0522.688.552
www.compac.it - info@compac.it

COMPANY WITH
SAFETY MANAGEMENT SYSTEM
CERTIFIED BY DNV GL
= ISO 45001 =

COMPANY WITH
ENVIRONMENTAL SYSTEM
CERTIFIED BY DNV GL
= ISO 14001 =

COMPANY WITH FOOD
SAFETY SYSTEM
CERTIFIED BY DNV GL
= ISO 22000 =

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =

