## containers in CA+PET

> containers in cardboard (CA) + polyethylene terephthalate (PET)







- Containers in PLA
   Containers in APET
   Containers in CA + PLA
   Containers in CELLULOSE (PULP)
   Containers in CA + PET
   Containers in PP
   Containers in CPET
   Containers in ALUMINIUM (ALc/ALbn)



## containers in CA+PET

## > containers in cardboard (CA) + polyethylene terephthalate (PET)

Our cardboard trays are produced from pure cellulose fiber coated with polyethylene terephthalate (PET) to make them waterproof and greaseproof.

The containers in CA+PET are thermo-sealable and are a paramount element of the COMPAC SYSTEM together with the tray sealers and the sealing film reels.

Are available containers generic printing instructions for use "multilingual" in Italian/English/French/German/Spanish. On request the containers can be customized (brands and logos, texts, colours).

RECYCLABLE CONTAINERS WITH PAPER - ATICELCA® 501 - level B



## Technical properties of our containers $(\mathbb{R}^n)$

- good mechanical properties (abrasion resistance, flexural strength, etc ... );
- high elasticity which make them safe from breakage during handling and transport;
- excellent resistance to aggressive chemical agents, to organic and inorganic substances (including oil, fat, etc;) and an excellent physiological behaviour (odourless, flavourless);
- suitable for reheating in microwave ovens or traditional ovens up to +200° C for 60 minutes;
- suitable for cooking by the consumer only if subsequent to the heat-sealing of the package with READY TO COOK food in a microwave ovens or traditional ovens up to + 200 °C for 60 minutes;
- suitable for frozen food down to a minimum temperature of  $-40^{\circ}$  C.

To identify and facilitate material selective separation, our containers in cardboard (CA+PET) are marked with the following logo: 🐴

They belong to the Compac line Kline



If collected, the containers can be recycled or incinerated.

Incineration would only produce usual compounds produced by paper and hydrocarbons combustion.







V45MC 750ml

Item	Series	(mm) LxBxH	\_ml_/	Pack X Pieces		B	H	
V45PC	P2	137 x 122 x 45	500	4 x 100	290	260	295	36
V33GC	G	192 x 140 x 33	500	4 x 100	400	300	300	24
V45GC	G	192 x 140 x 45	750	4 x 75	400	300	300	24
V75GC	G	192 x 140 x 75	1250	4 x 50	400	300	300	24
VS45HC	Н	214 x 142 x 45	950	4 x 150	400	300	450	16
V25LBC	L	232 x 192 x 25	/	2 x 125	400	280	250	24
V45LC	L	232 x 192 x 45	1500	2 x 100	400	400	290	24
V20MBC	М	262 x 192 x 20	/	2 x 125	400	395	250	24
V45MC	М	262 x 192 x 45	1750	2 x 100	400	400	290	24
V45XC	X	322 x 192 x 45	2250	2 x 100	400	400	340	12
V50ZCB	Z	325 x 265 x 50	3000	2 x 95	593	398	353	12

All technical data does not have scientific value and are reported only for the purpose technical / application of the product.

Technological suitability: the product must always be verified by the user as regards the technological suitability referring to the production process, the packaging environment and the food to be packaged.

Compac s.r.l. 42024 Castelnovo di Sotto - RE - Italy Tel. +39 0522.688.509 Fax +39 0522.688.552

CERTIFIED BY DNV GL

