

# containers in smooth wall aluminium (ALc)

containers in ALc

> smooth wall aluminium containers (ALc)



Compac s.r.l.  
Via Spallanzani 8/a  
42024 Castelnovo di Sotto - RE - Italy  
Tel. +39 0522.688.509 / +39 0522.683.873  
www.compac.it - info@compac.it

- Containers in PLA
- Containers in APET
- Containers in CA+PP
- Containers in CA + PLA
- Containers in POLPA
- Containers in CA + PET
- Containers in PP
- Containers in CPET
- Containers in ALUMINIUM (ALc/ALbn)

**CP**  
**COMPAC**  
P A C K A G I N G

# containers in smooth wall aluminium (ALC)


## > smooth wall aluminium containers (ALC)

Our SMOOTH WALL ALUMINIUM containers manufactured from lacquered foil are thermo-sealable and constitute an essential element of the COMPAC SYSTEM together with the tray sealers and the sealing film reels. Our containers are suitable for food packed in modified atmosphere with a long shelf life. Available in aluminium colour inside and black outside to enhance your product presentation.






## Technical properties of our containers

- suitable for pasteurisation and sterilization;
- excellent resistance to aggressive chemical agents, to organic and inorganic substances (including oil, fat, high salt or acid content etc...) and an excellent physiological behaviour (odourless, flavourless);
- providing the **best possible** barrier to gas for food with a long shelf life;
- ideal for ready to **cook** products and for reheating in microwave oven and traditional oven up to +200° C for 60 minutes;
- a sealable roasting pan: suitable for cooking food at a maximum temperature of 200°C for 60 minutes, the container can be sealed straight after;
- suitable for frozen food;
- our ALc containers can go directly from the freezer to the oven.

To identify and help material sorting, our containers are marked with the following symbol: 

This range is part of the Compac *Rline* . When collected, the containers can be recycled.



| Item    | Series | (mm)<br>LxBxH  | ml   |  Pack<br>x Pieces |  L |  B |  H |  |
|---------|--------|----------------|------|--|---|---|---|---|
| VA45Pc  | P2     | 142 x 126 x 45 | 500  | 4 x 160  | 400   | 295   | 276   | 24  |
| VA45Gc  | G      | 196 x 142 x 45 | 850  | 4 x 160  | 400   | 404   | 307   | 18  |
| VA40GLc | GL     | 197 x 155 x 40 | 860  | 4 x 120  | 405   | 305   | 320   | 24  |
| VA45Hc  | H      | 214 x 142 x 45 | 1000 | 2 x 160  | 400   | 295   | 234   | 32  |
| VA75Hc  | H      | 214 x 142 x 75 | 1300 | 2 x 110  | 400   | 295   | 234   | 32  |
| VA45Lc  | L      | 233 x 196 x 45 | 1550 | 2 x 160  | 400   | 404   | 252   | 24  |
| VA45Mc  | M      | 266 x 196 x 45 | 1800 | 2 x 160  | 400   | 404   | 283   | 18  |
| VA60Zc  | Z      | 322 x 262 x 60 | 3600 | 2 x 146  | 593   | 398   | 353   | 12  |

No responsibility is implied or may be linked to this catalog.

All technical data does not have scientific value and are reported only for the purpose technical / application of the product.

Technological suitability: the product must always be verified by the user as regards the technological suitability referring to the production process, the packaging environment and the food to be packaged.

Compac s.r.l.  
Via Spallanzani 8/a  
42024 Castelnovo di Sotto - RE - Italy  
Tel. +39 0522.688.509 / +39 0522.683.873  
www.compac.it - info@compac.it



COMPANY WITH  
FOOD SAFETY SYSTEM  
CERTIFIED BY DNV  
ISO 22000

COMPANY WITH  
MANAGEMENT SYSTEM  
CERTIFIED BY DNV  
ISO 9001 • ISO 14001  
ISO 45001

  
**COMPAC**  
P A C K A G I N G